




Description

DME PROLINK's range of Category 6A Copper Patch Leads are designed for optimal performance and manageability. Our Patch Leads are designed to offer a slim profile specifically for today's high-density environments. Snag-less plug design makes these Patch Cords an excellent choice in environments where moves, adds and changes (MAC's) are frequent.

Features & Benefits

- Meets all requirements specified in ANSI/TIA-568.2-D
- Low Smoke Zero Halogen
- Connector wiring T568B wire scheme.
- Fully interoperable and backwards compatible
- UL Listed and ETL Verified
- 25 Years System Warranty



TRANSMISSION PERFORMANCE

Near End Cross Talk	Meet all Requirements Specified in ANSI/TIA-568.2-D
Return Loss	Meet all Requirements Specified in ANSI/TIA-568.2-D

MECHANICAL

Plug	
Assembly	Compatible with FCC Part 68 Subpart F
Housing	UL Listed 94V-0 Flame-Retardant PC (Polycarbonate)
IDC Blades	Phosphor Bronze. Contact area of blades is plated with 50 micro- inches of hard gold over 100 micro-inches of Nickel
Cordage	
Construction	CM c(UL) CMG 70°C FT4 4Pair 26AWG ANSI/TIA-568.2-D CAT6A - --S/FTP LSZH

PHYSICAL

Plug Assembly	Polycarbonate, 94V-0, the contact Area of blades is plated with 50 micro- inches of hard gold over 100 micro-inches of Nickel
CAT6A Patch Cable	FR-PE Low Smoke Zero Halogen Jacket
Strain Relief	BASF TPU Low Smoke Zero Halogen

Part Number

D0233-UN1LSGY	Copper Patch Lead, CAT6A, Unshielded, 1m, LSZH, Grey
D0233-UN2LSGY	Copper Patch Lead, CAT6A, Unshielded, 2m, LSZH, Grey
D0233-UN3LSGY	Copper Patch Lead, CAT6A, Unshielded, 3m, LSZH, Grey
D0233-UN5LSGY	Copper Patch Lead, CAT6A, Unshielded, 5m, LSZH, Grey