



Description

DME PROLINK's has wide range of Dual Section Wall Mount cabinets which are available in any number of configurations to suit any environment or application.

Features & Benefits

- Removable Side panels and Doors for Easy access.
- Swing-out Type
- Glass or Perforated Metal Front and Rear door options. (Reversible)
- Top or bottom cable entry
- Fan Tray with 1 / 2 Fans
- Standard 6-Way Power Distribution Unit (PDU) comes with Cabinets. (PDUs can be customized)
- Key Lock arrangement for added security (3 Part Locking System for higher "U" cabinets)
- Height (H): 6U, 9U, 12U, 15U, 16U, 18U, 19U, 21U, 22U, 26U
- Width (W): 600mm
- Depth (D): 450mm, 500mm, 515mm, 550mm 600mm, 800mm
- Customizable Knockouts with rubber grommets
- 19" Mounting Rails complying with EIA-310D
- 25 Years System Warranty

Construction

SPCC Quality cold rolled steel (1.2mm Thickness)

Standards Compliance

- ❖ ANSI/EIA RS-310-D, IEC297-2, DIN41491; Part1, DIN41494; Part7, GB/T3047.2-92 Standard.
- ❖ Compatible with 19" international Standard and Metric Standard & ETSI.



Removable Side Panels with optional side panel lock



Cabinets Fans for Ventilation



Adjustable Mounting Rails



Cabinet Shelf



Switched 6-way PDU



Cable Entry Knockout



D 3 5 5 - h w d s p f c

h	Height
6	6U
9	9U
12	12U
15	15U
16	16U
18	18U
21	21U
22	22U
26	26U

w	Width
60	600mm

d	Depth
45	450mm
51	515mm
55	550mm
60	600mm
80	800mm

s	Number of Shelves
0	No Shelf
1	1 Shelf
2	2 Shelves

c	Color
WT	White
BK	Black
GY	Grey
BG	Beige

f	Fans
0	No Fans
1	1 Fan
2	2 Fans

p	Number of PDU's
0	No PDU
1	1 x 6-Way PDU
2	2 x 6-Way PDU's