

FIBER PANELS

Fiber Optic Patch Panel 19" Rack Mount, 3U, 144F, Unloaded

DME PROLINK
CONNECTING THE GLOBE



25
YEARS
SYSTEM WARRANTY



Product Description

DME PROLINK provides 19" Rack-mountable Fiber Optic Patch Panel for splicing and/or termination of optical fibers in an indoor environment. Also, loaded type available with Multimode or Single-mode pigtailed, splice accessories and adapters. The solution provides an optical channel that is guaranteed to be compliant with the ISO 11801 International Standard for Structured Cabling. DME PROLINK quality personals ensures product reliability through rigorous qualification testing to assure cable performance and durability in adverse field environments. Excellent quality control is achieved through intense in- house quality check and stringent audit acceptance by ISO 9001.

Features & Benefits

- 19" Rack-mountable: 3U
- Easy to install.
- Comes in Unloaded and loaded versions
- The body is made of cold-rolled steel
- Cable Fixing and Grounding Devices installed within Patch Panel
- Internal cable management
- Accommodates Splicing and/or Direct Termination
- Accepts DME PROLINK compliant adapters/couplers.
- Panels can be ordered configured.
- 25 Years System Warranty



Technical Specification

- Insulating resistance between the metal parts of the body and grounding fitting: $\geq 2 \times 10^4$ M Ω /500VDC
- Voltage Proof: 3000VDC
- Product Dimension for 3U: 483mm (W) X 132 (H) X 280mm (D)
- Working Temperature: Indoor Type : 5°C to +40°C; Outdoor Type: -25°C to +55°C
- Storage Temperature: -25°C to +55°C
- Relative Humidity \leq 95%

Part Number

D1219-1443EMN000BK

Fiber Optic Patch Panel, 144 Port (Unloaded), 3RU, 19 inch Rack mountable with in-built Splice Tray, Black