



Product Description

DME PROLINK Jumper Wire, 2 Conductor 0.6mm Bare Copper, PVC Insulation, Color Blue/White

Application

Used for telephone, power, Wiring harness connector

Certifications & Approvals

ISO9001, ISO14001, OHSAS18001
RoHS: Compliant Directive 2011/65/EU
CPR E class

Specification

Conductor Diameter	0.6mm
Conductor Material	Oxygen-free Bare Copper
Conductor Count / Total No. of Pair	2 / 1
Insulation Material	PVC – Polyvinyl Chloride
Insulation Sheath Thickness	0.25mm
Insulation Dia Nom. (± 0.1mm)	1.10mm
Insulation Colors	Blue / White
Operating Temperature Range	-20°C to +75°C
Max. Operating Voltage	300V
Packing Length (Meters)	500m Drum or 200m Paper Reel
Conductor Resistance	≤98.0 Ω/km

Part Number

D014-JW20.6PV5BW	DME PROLINK Jumper Wire, 2 Conductor 0.6mm Bare Copper, PVC Insulation, 500 meters, Blue/White
D014-JW20.6PV2BW	DME PROLINK Jumper Wire, 2 Conductor 0.6mm Bare Copper, PVC Insulation, 200 meters, Blue/White