

DME PROLINK® Wall Mount Terminal Enclosure (WMTE) with Profile Frame - IP40





IP 40

Application

Wall mounted Terminal Enclosure with profile frame for placement of LSA modules

Features & Benefits

- Lower installation costs
- Closed sheet steel Terminal Enclosure
- Door with swivel lever handle and 3-point locking system
- Double-bit insert Lock and keys
- Cable entry from above and below via brush strip with self-supporting back mount frame
- Front mounting drafted sheet steel door with secure hinge pins
- Door opening angle 180°
- Flexible horizontal and vertical jumper wire guides
 - Cable catch and shield contact in the back-mount frame
- Design specifically for wiring and routing level
- Equipotential and grounding of the door with grounding strap
- Wall mounting bracket kit included for fastening
- Document Holder

Туре	WMTE-170(100)
Protection Class	IP40
Material	Powder Coated Steel Plate
Dimension (WxHxD) in mm	400 x 600 x 220
Capacity	LSA DM & CM: 170 Pair (1 x 17 Modules)
Operational Temperature	-40°C to +60°C
Color	RAL 7035 (Light Grey)

Part Number

D067-IP40WMTE170YGYIP40 Wall Mount Terminal Enclosure with profile frame, Capacity LSA DM&CM: 170
pairs, Dimensions (WxHxD): 400x600x220 mm; RAL 7035 (Light Grey); Closed sheet
steel; For holding LSA modules for profile rods; Door with swivel handle and 3-point
locking System with Double-bit insert Lock and Keys

Variance

D067-IP40WMTE200YGY	IP40 Wall Mount Terminal Enclosure with profile frame, Capacity: 2 x 100 Pair, Number of Modules Slots: 1 x 12, Number of Row: 1; Dimensions (WxHxD): 600x600x220 mm; RAL 7035 (Light Grey)
D067-IP40WMTE500YGY	IP40 Wall Mount Terminal Enclosure with profile frame, Capacity: 2 x 250 Pair, Number of Modules Slots: 1 x 26, Number of Row: 2; Dimensions (WxHxD): 600x800x220 mm; RAL 7035 (Light Grey)
D067-IP40WMTE1350YGY	IP40 Wall Mount Terminal Enclosure with profile frame, Capacity: 3 x 450 Pair, Number of Modules Slots: 3 x 46, Number of Row: 3; Dimensions (WxHxD): 800x1300x220 mm; RAL 7035 (Light Grey)

LSA : Lötfrei Schraubfrei Abisolierfrei (no solder, no use of screws, no insulation removal) in German

Technical Assistance Middle East HQ: +971 (4) 8118000

www.dmeprolink.com